

























**ENERGY**  
Almost Fuel Oil  
Energy Saver  
\* Efficiency range 20-30%  
\* For more information, visit www.york.com

**AWARNING**  
RISK OF EXPLOSION AND  
FIRE. EXPLOSION AND  
FIRE DANGERS. READ AND  
UNDERSTAND ALL INSTRUCTIONS  
AND WARNINGS. ALWAYS  
USE PROPER WIRING  
PRACTICES. ALWAYS  
DISCONNECT ALL POWER  
BEFORE WORKING ON  
ELECTRICAL SYSTEMS.  
FOR SUPPLIES, VISIT  
WWW.YORK.COM

**AVERTISSEMENT**  
DANGER DE PEU D'EXPLOSION  
ET D'INCENDIE. LIREZ  
ATTENTIVEMENT LES  
INSTRUCTIONS ET LES  
AVERTISSEMENTS. TOUJOURS  
UTILISER LES BONNES  
PRATIQUES DE  
CABLAGE. TOUJOURS  
DÉCONNECTER TOUS  
LES ALIMENTATIONS  
AVANT DE TRAVAILLER  
SUR LES SYSTÈMES  
ÉLECTRIQUES. POUR  
LES FOURNISSEURS,  
VISITEZ  
WWW.YORK.COM

**ADVERTENCIA**  
RIESGO DE INCENDIO  
Y DE EXPLOSIÓN. LEA  
Y ENTENDEA TODAS  
LAS INSTRUCCIONES  
Y ADVERTENCIAS. SIEMPRE  
UTILICE LAS BUENAS  
PRÁCTICAS DE  
CABLEADO. SIEMPRE  
DESCONECTE TODA  
ALIMENTACIÓN ANTES  
DE TRABAJAR EN  
LOS SISTEMAS  
ELÉCTRICOS. PARA  
PROVEEDORES, VISITE  
WWW.YORK.COM

FR 08161871-1-1

3/4" CRELINE PVC SCH 40 180 PSI

FR-08161871-1-1







**Aprilaire**  
 Model 1820  
 70 HERTZ

110/120VAC, 60 Hz  
 MAX NORMAL OPERATING AMPS: 6.7 A  
 COMPRESSOR LOCKED MOTOR AMPS: 31A  
 COMPRESSOR RATED LOAD AMPS: 5.26A  
 FAN RATED POWER: 77W  
 THERMALLY PROTECTED MOTOR  
 REFRIGERANT: R134a, 18.3 oz  
 MAXIMUM DESIGN PRESSURE: 276psi (19.0 bar) LHM 1/4"

US PATENTS:  
 5,547,817; 5,981,288; 5,491,288; 7,074,871

CANADIAN PATENTS:  
 22,245,125 AND OTHERS PENDING

SERIAL NO: 45222842013

**RP** RESEARCH PRODUCTS CORPORATION  
 BRISTOL, WI 53003

**⚠ WARNING** RISK OF ELECTRIC SHOCK. CAN CAUSE INJURY OR DEATH. DISCONNECT ALL REMOTE ELECTRIC POWER SUPPLIES BEFORE SERVICING.

**⚠ AVERTISSEMENT** RISQUE DE CHOCS ÉLECTRIQUES. PEUT CAUSER DES BLESSURES ET MÊME ENTRAÎNER LA MORT. COUPER LES SOURCES D'ALIMENTATION À DISTANCE AVANT LE DÉPANNAGE.

**⚠ CAUTION** MOVING PARTS. HOT... OPERATE UNIT WITH ACCESS...



1-VA 300V VWT  
 X0.824mm(718AWG) 300V VWT



FILTER ACCESS  
WARNING  
& CAUTION  
ATTENTION



1. Unplug the dehumidifier from the power outlet.  
2. Turn the dehumidifier upside down.  
3. Remove the filter cover.  
4. Remove the filter.  
5. Wash the filter in warm water.  
6. Rinse the filter thoroughly.  
7. Allow the filter to dry completely.  
8. Reinsert the filter and replace the cover.  
9. Plug the dehumidifier back into the power outlet.









